




P.O. Box 3365 South El Monte, CA 91733 626.444.0541 Fax 626.444.3887 www.Afcon.org

552

TAPPED BRACKET



SIZE - 3/8" rod.

MATERIAL - Carbon Steel.

FINISH - Plain or E.G.

LISTING/APPROVAL -

cUL_{us} 203 - EX 2551


FUNCTION - Listed to support max. 4" Steel, CPVC or Copper pipe.
Listed hanger component per NFPA 13.

INSTALLATION - per NFPA 13. Space by pipe type.
Install on vertical mounting surface of wood, concrete or steel.
Center hole accepts 3/8" and 1/2" NFPA 13 fasteners.

ADDITIONAL UL LISTED FASTENERS PER NFPA 13 FOR STEEL PIPE LOADS -SEE TABLES..

FEATURES


- * Tapped rod hole.
 - * Double fastener installation allows:
 - Vertical - Hangs plumb from first fastener.
 - Stops wood splitting along the grain.
 - * **No speed/pal nuts** required.
- ORDERING** - Part # and finish.



553 BRACKET

Wood - No Pre Drill			Steel - 1/4" or #14 Tek		
Min. Fastener	Min. Qty.	Max. Pipe	Min. Thickness	Min. Qty.	Max. Pipe
#14x1 1/2 S.M.S.	1	2	14 GA.	1	3
#14x2 S.M.S.	2	4		2	4
1/4 x 2 L.B.	1	2 1/2	16 GA.	1	2
1/4 x 2 L.B.	2	4		2	3
#16x2 D.S.	2	2	18 GA.	2	2 1/2

W.S.= Wood Screw
D.S.= Drive Screw
S.M.S. = Sheet Metal Screw
L.B.= Lag Bolt



SIZE - 3/8" rod

MATERIAL - Carbon Steel.

FINISH - Plain or E.G.

LISTING/APPROVAL -

cUL_{us} 203 - EX 2551

NOTE - Criteria same as 552 above except 13/32" rod hole.
Install hanger rod with 3/8" nut.

